

DESIGNED TO KEEP YOUR WORKFLOW MOVING




imageFORCE 1440 delivers high-quality performance in a compact, space-saving frame. Designed for simplicity and speed, it prints up to 40 ppm (A4, single-sided) and features advanced security to keep your operations running smoothly.



EASY OPERABILITY

Organise your print jobs using dedicated tabs and tailor each one easily with an intuitive drag-and-drop feature.



Print File from Server

Simplify everyday workflows by printing files directly from shared folders with a single tap.



Connectivity

Enjoy greater productivity with uniFLOW Online. Print effortlessly from any device via AirPrint or Mopria to keep your workflow uninterrupted.



SECURE AND RELIABLE

The 1440 comes with the latest security features, giving you peace of mind to focus on driving business results.



Encrypted Secure Print

Prevent data leaks by ensuring print jobs are securely encrypted before being sent to the device.



User Authentication

Restrict access to verified and approved users only to minimise the risk of data breaches.



Verify System at Start Up

Checks the firmware and application integrity during device startup.

imageFORCE 1440 series Specifications

Main unit

Machine type

1440: Monochrome A4 Laser Multifunctional

Core functions

1440: Print, Copy, Scan, Send

Control Panel

5 inch TFT LCD WVGA Colour Touch panel

Memory

Standard: 1.0GB RAM

Storage

2GB

Interface connection

Network
Standard:
1000Base-T/100Base-TX/10-Base-T,
Wireless LAN (IEEE 802.11 b/g/n),

Others

Standard:

USB 2.0 (Host) x2, USB 2.0 (Device) x1

Memory Media:

USB Memory

Paper supply capacity (A4, 80gsm)

Standard: 250 sheets
Paper Cassette: 550-sheet
Multi-purpose tray: 100-sheet
Maximum: 900 sheets
(with Cassette Feeding Module-AH1x1)

Paper output capacity (A4, 80gsm)

Standard: 65 Sheets

Supported media types

Upper Cassette 1:
Thin, Plain, Thick, Recycled, Colour,
Bond, Letterhead, Label, PostCard,
Envelope

Multi-purpose tray:
Thin, Plain, Thick, Recycled, Colour,
bond, Letterhead

Supported media sizes

Upper Cassette 1:
Standard size: A4S, B5S, A5L, A5S, A6S,
LTRS, LGLS, STMTS, EXES, OFICIO, S,
B-OFICIO, S, M-OFICIO, S, GLTRS, GLGLS,
FLS-S, AFLS-S, indianLGLS
Custom size: 105.0 x 148.0 mm up to
216.0 x 355.6 mm

Multi-Purpose tray:

Standard size: A4S, B5S, A5L, A5S, A6S,
LTRS, LGLS, STMTS, EXES, OFICIO, S,
B-OFICIO, S, M-OFICIO, S, GLTRS, GLGLS,
FLS-S, AFLS-S, indianLGLS, Envelopes
[No. 10 (COM 10), Monarch, ISO-C5, DL]
Custom Size: 76.2 x 127.0 mm up to
216.0 x 355.6 mm

Supported media weights

Upper Cassette 1: 60 to 120 gsm
Multi-purpose tray: 60 to 199 gsm
Duplex: 60 to 120 gsm

Warm-up Time (Quick start mode:N/A)

From Power On: 14 Seconds or Less¹

¹ 1440: Time from device power-on,
until copy ready (not print reservation)

From Sleep Mode: 4 Seconds or Less

Dimensions (W x D x H)

1440: 420 x 460 x 375 mm

Installation Space(W x D)

1440: 420 x 881 mm*

*Cassette and back door opened

Weight* without toner

1440: Approx. 16.2 kg

Print Specifications

Print Speed (BW)

1-sided : 40 ppm (A4)
2-sided : 33 ppm (A4)

Print Resolution (dpi)

600 x 600

Page description languages

Standard: UFR II, PCL6, PCL5,
Adobe PostScript 3

Direct Print

Direct printing available from
USB memory
Supported file types: TIFF, JPEG, PDF

Printing from mobile and cloud

Application

AirPrint, Canon PRINT, Mopria® Print
Service, and uniFLOW Online, Universal
Print

OS Standard Printing

Android/Windows® 11/ Chrome OS/
macOS (11.2.2)/ iOS/ iPadOS

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2
OCR fonts, Barcode fonts*
PS fonts: 136 Roman

*Require optional BARCODE PRT KIT-E1

Operating system

UFR II: Windows® 11, Server 2016/
Server 2019/Server 2022/Server 2025
mac OS (10.15 or later)

PCL: Windows® 11, Server 2016/
Server 2019/ Server 2022/ Server 2025
mac OS (10.15 or later)

PS: Windows® 11, Server 2016/
Server 2019/ Server 2022/ Server 2025
mac OS (10.15 or later)

PPD: Windows® 11, mac OS X
(10.15 or later)

Copy Specifications

Copy Speed

1-sided : Up to 40 ppm (A4)
2-sided : Up to 33 ppm (A4)

First-Copy-Out Time (BW)

Approx. 6.1 seconds or less (A4)

Copy resolution (dpi)

300 x 600 (DEF)
600 x 600

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments)
Preset reduction/enlargement: 25%,
50%, 70%, 100%, 141%, 200%, 400%

Send Specifications

Destination

E-mail/ Internet FAX (SMTP), SMB, FTP

Address Book/Speed dials

LDAP (50)/Local (300)/Speed dial (281)

Send resolution (dpi)

Push: 192 x 204 (I-FAX)
300 x 300 (email/SMB/FTP)
Pull: Max. 9600 x 9600

Communication protocol

File : FTP (TCP/IP), SMB3.0 (TCP/IP)
Email/iFax: SMTP (Send), POP3 (Receive)

File Format

Standard:TIFF, JPEG*,
PDF (Compact, Searchable),
Optional: PDF(Encrypted, Digital
Signature)
*Single Page Only

Scan Specifications

Type

Standard: Single-Pass Duplexing
Automatic Document Feeder

Document Feeder Paper Capacity (A4, 80gsm)

Up to 50 sheets

Acceptable Originals and weights

Platen: Sheet, Book

Document Feeder sheet media weight :

1-sided/2-sided continuous scanning:
50 to 105 gsm

Supported media sizes

Sheet media size:
A4S • B5S • A5S • A6S
Custom size:
48.0 x 85.0 to 216.0 x 355.6 mm

Scan Speed (ipm: BW/CL; A4)

Copy (300 x 600 dpi):
1-sided Scanning (BW): 40
1-sided Scanning (CL): 20
2-sided Scanning (BW): 80
2-sided Scanning (CL): 40

Send(300 x 300 dpi):

1-sided Scanning (BW): 50
1-sided Scanning (CL): 40
2-sided Scanning (BW): 100
2-sided Scanning (CL): 80

Scan Resolution (dpi)

Scan for Copy: up to 600 x 600
Scan for Send: (Push) up to
300 x 600, (Pull) up to 600 x 600

Pull Scan Specifications

ScanGear MF For both TWAIN
and WIA, Mac OS (10.15 or later)

Environmental Specifications

Operating environment

Temperature: 10 to 30°C
Humidity: 20 to 80 % RH (Relative
Humidity)

Power source

220-240V, 50/60Hz, 3.1A

Power consumption

1440: Maximum: Approx. 1280W or less
Standby: Approx. 8.0 W*¹
Sleep mode: Approx. 0.9 W*²

*¹ Reference value: measured one unit

*² Sleep mode is not available in all circumstances
due to certain settings

Consumables

Toner Cartridge/s

Toner T13 Black

Toner Yield

Black: 10,600* impressions (A4)

* Toner cartridge yield is in accordance with ISO/IEC 19752



Trellix

To arrange for a demonstration, simply contact any of our offices below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

Partner / Dealer Stamp

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, MEAP, eMaintenance, iW, Business can be simple and Canon Genuine Toner, Cartridge & parts are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and therefore are independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2025 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore