

COMPACT POWER THAT *DELIVERS WHEN IT MATTERS*



Canon imageFORCE C611 Series is designed for businesses that need high-speed A4 colour printing without compromising office space.

With a compact frame, these devices produce fast, quality colour prints to help you keep pace with busy office demands. Split-zone fuser technology heats only where needed, boosting speed while reducing energy consumption.

Cloud storage connectivity ensures your business can share and access documents securely for complete workflow efficiency.



CONNECTIVITY

Get the option to access cloud platforms like Google Drive and Dropbox directly from the device. Enjoy mobile printing with Canon PRINT, Apple AirPrint and more for ultimate convenience.



SECURITY

Advanced protection for your data, with features like user authentication and audit logs that help you monitor and mitigate potential risks.



RELIABILITY

Engineered for optimal performance, with intelligent maintenance tools and long-lasting parts that reduce downtime and maximise uptime.



SUSTAINABILITY

Built with up to 24% recycled plastic, supported by eco-friendly packaging and lower energy consumption.

imageFORCE C611 Specifications

Main Unit

Machine type

A4 Colour Laser Multifunctional

Core functions

Print, Copy, Scan, Send, Store and Optional Fax

Processor

Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Colour Touch panel

Memory

RAM: 4.5GB

Storage

SSD: 256GB

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T
Optional: Wireless LAN (IEEE 802.11a/b/g/n/ac/ax)

Others

Standard: USB 2.0 (Host) x 1, USB 3.0 (Host) x 1,
USB 2.0 (Device) x 1
Optional: Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)

Standard: 650 sheets
100-sheet Multi-purpose tray x 1
550-sheet Paper cassette x 1
Maximum: 2,300 sheets (with 2 x Cassette
Module-AL1 + 1 x Cassette Feeding Unit-BA1)

Paper output capacity (A4, 80gsm)

400 sheets

Supported Media Types

Multi-purpose tray:
Thin, Plain, Heavy, Recycled, Color, Transparency,
Envelope, Bond,
Letterhead, Labels

Paper Cassette:

Thin, Plain, Heavy, Recycled, Color, Pre-punched,
Bond, Letterhead, Labels

Supported Media Sizes

Multi-purpose tray:
Standard size: A4, A5, A5R, A6, B5
Custom size: 76.0 x 127.0 mm to
216.0 x 355.6 mm
Envelopes: COM10 No.10, Monarch, DL, ISO-C5
Envelope custom size: 76.0 x 127.0 mm to
216.0 x 355.6 mm
Paper Cassette:
Standard size: A4, A5, A5R, A6, B5
Custom size: 101.6 x 148.0 mm to
216.0 x 355.6 mm

Supported media weights

Multi-purpose tray: 60 to 216 gsm
Paper Cassette: 60 to 163 gsm
Duplex: 60 to 163 gsm

Warm-up Time

Quick Startup Mode: 4 Seconds or less*
* Time from device power-on to when the copy icon
appears and is enabled to operate on the touch panel
display.

From Power On: 10 seconds or less*

* Time from device power-on, until copy ready
(not print reservation)

From Sleep Mode: 10 Seconds or less

Dimensions (W x D x H)

500 x 620 x 645 mm

Installation Space(W x D)

Basic:
866 x 847 mm (with left cartridge door & right door
open + front cassette open)

Weight*

*including regular toner
Approx. 47 kg

Print Specifications

Print Speed (BW and CL)

imageFORCE C611
1-sided: Up to 61 ppm (A4), Up to 85 ppm (A5R),
Up to 99 ppm (A5), Up to 69 ppm (A6)

imageFORCE C521

1-sided: Up to 52 ppm (A4), Up to 72 ppm (A5R),
Up to 84 ppm (A5), Up to 69 ppm (A6)

imageFORCE C431

1-sided: Up to 43 ppm (A4), Up to 60 ppm (A5R),
Up to 69 ppm (A5, A6)

imageFORCE C331

1-sided: Up to 33 ppm (A4), Up to 60 ppm (A5R),
Up to 69 ppm (A5, A6)

Print Resolution (dpi)

1,200 × 600
(*Data processing is 9,600 equivalent x 600, 1,200 x 1,200
equivalent (low speed))

Page description languages

Standard: UFR II, PCL6/PCL5, Adobe PostScript 3

Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

Printing from mobile and cloud

AirPrint, Mopria® Print Service, IPP Everywhere,
Canon PRINT, uniFLOW Online, Universal Print and
Cloud Connector

OS Standard Printing

Android/Windows® 11/Chrome OS/macOS (11.2.2
or later) /iOS (15.2 or later)/iPadOS

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T*1 (Japanese, Korean,
Simplified and Traditional Chinese), Barcode
fonts*2

*1 Optional PCL International Font Set-A1 is required.

*2 Optional Barcode Printing Kit-D1 is required.

Operating System

UFR II:
Windows® 11/Server2016/Server2019/Server2022/
Server2025, macOS (10.14 or later)

PCL:

Windows® 11/Server2016/Server2019/Server2022/
Server2025

PS:

Windows® 11/Server2016/Server2019/Server2022/
Server2025, macOS (10.14 or later)

PPD: Windows® 11, macOS (10.15 or later)

As of Dec. 2024

Copy Specifications

Copy Speed (BW and CL)

imageFORCE C611
1-sided: Up to 61 ppm (A4), Up to 85 ppm (A5R),
Up to 99 ppm (A5), Up to 69 ppm (A6)

imageFORCE C521

1-sided: Up to 52 ppm (A4), Up to 72 ppm (A5R),
Up to 84 ppm (A5) Up to 69 ppm (A6)

imageFORCE C431

1-sided: Up to 43 ppm (A4), Up to 60 ppm (A5R),
Up to 69 ppm (A5, A6)

imageFORCE C331

1-sided: Up to 33 ppm (A4), Up to 60 ppm (A5R),
Up to 69 ppm (A5, A6)

First-Copy-Out Time (A4, BW/CL)

imageFORCE C611
Approx. 4.3/4.7 seconds or less

imageFORCE C521

Approx. 5.0/5.4 seconds or less

imageFORCE C431

Approx. 5.7/6.3 seconds or less

imageFORCE C331

Approx. 5.7/6.3 seconds or less

Copy resolution (dpi)

600 x 600, 300 x 600

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)]

* Multi-Sheet Feed Detection is supported

Document Feeder Paper Capacity (80 gsm)

up to 100 Sheets

Document Feeder acceptable paper weight

Document Feeder media weight:

1-sided scanning: 42 to 128 gsm (BW),
64 to 128 gsm (CL)

2-sided scanning: 50 to 128 gsm (BW),
64 to 128 gsm (CL)

Note:

Business card: 80 to 220 gsm

Original width narrower than A6 except business card:
50 to 128 gsm

Supported media sizes

Platen scanning size: up to 216.0 x 355.6 mm

Document Feeder media size:

A4, A5R, A6, B5

Custom size: 48.0 x 128.0 mm to
216.0 x 355.6 mm

Business card: 48.0 x 85.0 mm to
55.0 x 91.0 mm

Scan Speed (ipm: A4)

Send (300 x 300 dpi):

Automatic Colour Select "OFF":

1-sided Scanning: 95

2-sided Scanning: 190

Automatic Colour Select "ON":

1-sided Scanning: 50

2-sided Scanning: 100

Copy:

Scan Speed Priority (300x600dpi: default)

1-sided Scanning: 50

2-sided Scanning: 100

Image Quality Priority (600x600dpi)

1-sided Scanning: 30

2-sided Scanning: 50

Scan Resolution (dpi)

600x600

Pull Scan Specifications

Colour Network ScanGear2 for both TWAIN and WIA

Supported OS: Windows® 11/Server 2016/Server
2019/Server 2022/Server 2025

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP*), SMB, FTP,
WebDAV, Mail Box

Optional: Super G3 FAX, IP Fax

* Available OAuth 2.0 authentication method on Microsoft
365 and Google Workspace

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Communication protocol

File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3

File Format

TIFF (MMR), JPEG, PDF (Compact, Searchable,
Optimize for Web, PDF/A-1b, Trace & Smooth,
Encrypted, Device Signature, User Signature), XPS
(Compact, Searchable, Device Signature, User
Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine),
200 x 200 (Fine), 200 x 100 (Normal)

Sending/Receiving Size

Sending: A4, A5R*, A6*, B5*

Receiving: A4, A5, A5R, B5

* Sent as A4

FAX memory

Up to 30,000 pages (2,000 jobs)

Speed dials

Max. 200

Group dials/destinations

Max. 199 dials

Sequential broadcast

Max. 256 addresses

Memory backup

Yes

Store Specifications

Mail Box (Number supported)

100 User Inboxes,

1 Memory RX Inbox,

50 Confidential Fax Inboxes

Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows® 10/11

Concurrent Connections (Max.): SMB: 64,
WebDAV: 3

Advanced Box available disc space

Standard: 16 GB

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH

(Relative Humidity/No condensation)

Power source

220-240 V, 50/60 Hz, 4.9 A

Power consumption

Maximum: Approx. 1,760 W

Sleep mode: Approx. 0.8 W*

* 0.8 W sleep mode is not available in all circumstances
due to certain settings.

Consumables

Toner Cartridges

Toner 1006 BK/C/M/Y

Toner Yield

Toner 1006 BK: 29,700 pages (A4)

Toner C/M/Y: 27,800 pages (A4)

* Toner cartridge yield in accordance with ISO/IEC 19798

Configuration Output Options*



Paper Feed Options



/ Cassette Module – AL1

- Supports up to A4
- Media Weight 60-163 gsm
- 550 sheets(80gsm)
- Up to 2 cassettes can be installed



/ Cassette Feeding Unit – BA1

- Supports up to A4
- Media Weight 60-163 gsm
- 550 sheets(80gsm)

*Paper capacity may vary with different paper type/size.



Partner / Dealer Stamp

To arrange for a demonstration, simply contact our office below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2025 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.