

imagePRESS V1350

Canon

Delighting You Always



COLOUR PRODUCTION DIGITAL PRESS

Business Can Be Simple



Lightning-Fast Print
Speed up to 135 ppm



Extensive Support
for Rigid Stocks



Automated
Self-Adjusting
Colour and
Registration



Dependable
and Stable
Operation

Designed with **commercial printing** in mind

Consistently producing beautiful prints on time and within budget is no small task. That's why you need a partner with vision.

Say hello to the imagePRESS V1350 digital press. This high-volume, colour production digital press offers a seamless combination of powerful print productivity and labor-saving automation technology, and it's been designed to help produce beautiful, accurate prints easily and efficiently.

Canon technology can work to quickly and reliably produce offset-quality output and incredible repeatability. This flagship imagePRESS printing solution is designed to deliver astonishing print speeds of up to 135 ipm. The Active Registration Technology keeps paper aligned and moving through the press fluidly, minimizing downtime. Inline Spectrophotometers (ILS) can help operators to quickly produce repeatable, accurate color at the push of a button. The flat and stable paper path combined with the steel frame helps contribute to a press that's durable and reliable day in and day out. Plus, all this comes with expanded support for printing on a wide variety of medias up to 500gsm.

At the core of the imagePRESS V1350 are powerful technologies that can help our operation run efficiently. This workhorse is designed to deliver outstanding results that will not only exceed your customers' expectations, but keep them coming back for more.



Robust output and productivity with solid stability

DURABLE. RELIABLE. STABLE.

The imagePRESS V1350 is not just a productive press. Canon analyzed many areas of the engine to help ensure that image quality and dependability remain at a high level.



Flat, Stable Paper Path



Reinforced Units



Strong Steel Frame



High Part Life



Powerful productivity Magnificent quality

OUTSTANDING PRODUCTIVITY

Boost your output

Turn jobs around quickly with lightning-fast print speeds of up to 135 ipm (A4) with POD-SURF (Surface Rapid Fusing) Technology. The ILS allow operators to rapidly profile medias with the push of a button and, once running, the core imaging, color, and registration technologies take over, making real-time adjustments while maintaining high productivity throughout the run.

Expand your horizons

Offer customers more with expanded support for a spectrum of media, including thick, coated, and specialty stocks. The imagePRESS V1350 can easily handle a wide variety of jobs, from mixed media booklets and market collateral jobs to direct mail and light packaging work, all on stocks up to 500gsm. Cover and with brilliant color and clarity. Expand your horizons and easily grab the attention of the reader with the ability to print on large-size envelopes, labels, and synthetic and embossed stocks.

Minimize downtime

Vacuum Feed and Air Separation help to ensure your stocks are reliably fed into the press. Double-Sheet Detection* automatically diverts these jam-prone pages to a dedicated purge tray, without stopping the press or requiring operator attention.

The Active Registration System utilizes a steel side plate to help keep paper aligned correctly and provide tight and consistent registration.

And media is kept running smoothly through the press with a flat paper path and Canon's Media Conditioning Technology, which minimizes curl, exiting the press neatly stacked and ready for finishing.

Free up your staff

These advanced technologies combine to help keep your presses running fluidly, save you time, reduce waste, and free up operators so work can get out the door quickly and efficiently.

The imagePRESS V1350 offers a synergy of advanced print technologies designed to produce brilliant output efficiently, accurately, and effortlessly.

* POD Deck-E1 required.





SUPERB COLOR AND IMAGE CLARITY

Keep quality under control

Canon develops advanced print technologies that can help you produce brilliant colour and keep it stable throughout production runs. While the ILS offer automation to colour calibration, media profiling, and verification processes, Multi D.A.T. takes over during production by automatically measuring a range of highlight-to-shadow density patches between each sheet for real-time colour correction. Then let the optional Sensing Unit automate color accuracy checks, front-to-back alignment, and secondary transfer adjustments to help you achieve consistent output with brilliant colour that's delivered easily and fast.

Get the details right

Quality isn't about vibrant color alone; it's reflected in the clarity and detail of halftone images, vector artwork, and text. The short wavelength of Canon's R-VCSEL Laser is a key piece, helping to keep curves smooth, raster images clean, and text looking crisp. And while the first impression on the drum always looks strong, the Multi Exposure Technology hits every dot twice, helping to ensure that, as the drum ages, quality and clarity can remain at a high level.

Stay consistent

Getting consistent results on a wide range of media can be challenging. The Advanced Image Transfer Belt presses the toner into the media, allowing toner to fill in the peaks and valleys of textured stocks. Repeatable, accurate colour and high-density images are reliably produced for custom and premium applications. With the Translucent CV Toner, the surface properties of your media can shine through for consistent output that rivals offset printing.

Stand out from the pack

The imagePRESS V1350 colour production digital press has been engineered to perform in today's challenging commercial print marketplaces. You can have outstanding productivity and automation features, with brilliant image quality—and all with minimal operator involvement.



Brilliant **technology**

Sensing Unit*

With just the push of a button, the Sensing Unit sets up jobs to adjust color tone accuracy and front-to-back registration before printing. It can then help monitor and maintain these settings across a print run, continuously adjusting on the fly.

ILS (Inline Spectrophotometers)

This technology performs advanced color adjustments such as engine linearization, media calibration, color profile creation, and color validation—all with a touch of your finger.

Active Registration System

The combination of a steel side guide, front-edge detection, media positioning, and image timing sensors helps to produce tight and consistent front-to-back registration.

Twin Sleeve Developer

Multiple grooved rollers apply toner to the imaging drum, helping to produce consistent, rich solids across each sheet.

POD-SURF (Surface Rapid Fusing) Technology

An innovative fuser permits printing at speeds of up to 135 ppm (A4) and high productivity on mixed-media jobs.

R-VCSEL Imaging Laser

Canon's advanced 32-beam R-VCSEL Laser delivers 2400 x 2400 dpi print resolution, outputting detailed color images with outstanding definition at high speeds.

Multi-Exposure Technology

The R-VCSEL Laser writes every dot on the drum twice, which helps maintain high image quality consistently across long production runs.

Multi D.A.T.

Twenty (20) multi-gradation density patches are measured and corrected automatically during production, helping to provide consistent halftones.

ILS (Inline Spectrophotometers)

This technology performs advanced color adjustments such as engine linearization, media calibration, color profile creation, and color validation—all with a touch of your finger.

Paper Conditioner Technology

This prepares media for inline and offline finishing by minimizing curl to help preserve image quality and limit both jamming and reprints.

Translucent CV Toner

This helps produce consistent, vivid, and crisp images on a wide range of smooth and textured media with a realistic, offset-like finish.

Advanced Image Transfer Belt

The durable, flexible surface assists with pressing the translucent CV Toner onto smooth and textured surfaces to help minimize mottling and produce brilliant output.

Vacuum Feeding

This helps provide reliable feeding of heavy and coated paper, which aids in reducing potential misfeeds and downtime while printing.

POD Deck*

These vacuum-fed trays have a combined capacity of 9,000 sheets*, allowing jobs to run with minimal interruption.

Double-Sheet Detection with Purge Tray^Δ

An ultrasonic sensor detects air between sheets and, when detected, diverts the sheets to the top escape tray to help maintain throughput.

* Optional.

+ Capacity based on 80gsm.

^Δ POD Deck-E1 required.





Finish the job **beautifully**

Now you can deliver professionally finished products with the strong, inline capabilities and extensive optional integrated solutions from Canon.

FINISHING OPTIONS



Document Insertion Unit

This module enables insertion of slip sheets or preprinted covers for booklets and complex jobs.



Perfect Binding

Using hot glue, this module binds covers to book blocks of up to 400 pages* and can trim on all three sides for full-bleed books or manuals.



Professional Punching and Creasing

The many die patterns offered for in-line hole punching (including double punching) and creasing help minimize toner cracking on the spines of saddle-stitched booklets.



High-Capacity Stacking

Realize maximum productivity with unload-while-run capability, helping to provide uninterrupted printing with stacking up to 6,000 sheets*.



Ring Binding

Utilize the GBC eWire Pro or Max Ring Binder to automate the time-consuming process of wire binding manuals, booklets, and reports.



Booklet Trimming

Help maintain high productivity with a large-capacity trim waste bin and on-the-fly waste removal for continuous production. These modules can combine with the Booklet Finisher to help users produce professional, full-bleed booklets in-line.



Paper Folding

Offer promotional pamphlets, brochures, and more with the ability to produce Z-fold, C-fold, accordion fold, and double-parallel fold documents.



Professional Booklet-Makers

Deliver professional-looking, lay-flat booklets with speed and simplicity using the SDD BLM300C for booklets up to 120 pages* or the Plockmatic BLM50/35 for up to 200-pages* professional square-folded saddle-stitched booklets.

FEEDING OPTIONS



POD Deck

Equipped with vacuum feeding and air separation, each drawer supports up to 13" x 19.2" and 190 lb. Cover. Up to two POD Decks can be attached, increasing the capacity to 9,000 sheets.*

* Capacity based on 80 gsm.

Powerful, intuitive tools that can deliver amazing results



PRISMAsync Print Server

High performance and remarkable efficiency are yours with the PRISMAsync print server's impressive colour tools and G7® grayscale calibration.

Canon's PRISMAsync print server can help boost production capacity and lower costs. It helps deliver high-performance, deadline-driven printing that can assist with growing your business and nurturing successful relationships.

The **PRISMAsync Automated Color Task** feature combines multiple colour setup functionalities into a single action. The ILS allow for automated press linearization, G7® media calibration and profile creation, and verification procedures to be done quickly and easily for hands-off automation.

Embedded in-RIP G7® calibration utilizes the ILS to allow operators to calibrate, profile, and verify the colours of the imagePRESS V1350 digital press to help achieve a near-neutral print condition quickly and easily.

Pixel Precise Preview adds flexible color-correction capabilities, such as CMYK curve editing and digital moiré reduction with immediate visual feedback.

PRISMAsync Remote Manager allows you to monitor multiple presses and edit job properties, manipulate colour curves, manage queues, and submit and reroute print jobs.

Job Scheduler helps you manage your daily workload with up to eight hours of plan-ahead production. It displays the completion time of jobs and alerts you when interventions for media, toner, or staples are upcoming. The visual interface also makes prepress and production tasks clear.

The PRISMAlytics Dashboard puts recorded press data at your fingertips. This helps reduce turnaround time, waste, and costs by giving you access to detailed information on your usage, production, and consumption.



Efficiently manage prepress and colour with flexible workflows

The Fiery® print server's easy-to-use, familiar interface and smart colour-management technology offer endlessly flexible solutions.

imagePRESS Server E9000

Powered by the Fiery FS500 Pro system software and combined with the innovative Fiery HyperRIP feature, you can help improve the processing time for complex and graphic-intensive jobs.

The imagePRESS Server E9000 introduces new and upgraded technologies to familiar workflow and prepress features. Together, they further enhance the Fiery tools for workflow automation and advanced colour management.

Fiery's 1-Step Colour Manager allows users to calibrate and create a media profile for fast, easy, and reliable colour management while **Zero Step Calibration** checks each job's paper calibration timer to recalibrate, if necessary, before printing. And the **imagePRESS ILS** can perform both these functions as well as initialize press linearization and Spot Pro Optimization.

Media Librarian—Canon's sophisticated paper management application—creates, edits, and organizes paper stocks from a single, intuitive interface.

Fiery Job Expert analyzes incoming PDF files and dynamically chooses the ideal print settings to help achieve high print quality and optimize processing time.

Fiery Preflight Pro* permits users to verify file compliance against many industry standards—and view warnings and error messages in an interactive report.

Fiery JobFlow Base automates job preparation steps in prepress workflows to help produce print-ready files quickly and easily, which can increase productivity and reduce costs.

PRISMAsync SERVER

Optional/Standard

Optional

Print Resolution (dpi)

1200 x 1200, 600 x 600

Page Description Language(s)

PS3(Document Printing Mode)/
PCL, IPDS
(Transaction Printing Mode)

Memory

16GB

Hard Disk Storage

500GB + 1TB

Processor Speed

Intel Core i7-8700

System

Mark 9

Fonts

139 Type 1 fonts for Roman languages;
User import of PS fonts via Settings
Editor;
Optional Adobe Asian fonts:
Japanese: 5 fonts
Chinese: 2 fonts for simplified Chinese,
1 font for traditional Chinese;
Korean: 1 font for Korean

Supported Operating Systems

Windows 8.1 (32/64bit) and 10, Server
2012 R2, 2016, 2019, MacOS 10.15 (64
bit), MacOS 11, MacOS 12

Interface

Ethernet 10/100/1000BaseT x 2
USB3.0x8

Network protocols

TCP/IP, IPv6 Support, IPSec,
NetBEUI/SMB (hotfolders), secure
IPP, SNMP V3, Job MIB, HTTP, HTTPS,
Socket printing

Direct Print

PDF, JDF

VDP

PDF/VT-1, PPML

PRISMAsync Controller

PS/PDF, Scheduler, Multiple Queues/
hotfolders, Streaming, Accounting,
Scanning, PPML,
Standard Features
Remote Manager, Remote Service,
Integrity checker

PRISMAsync Controller Options

E-shredding, Advanced Colour
Management, Advanced Impose,
DocBox, Page Programming, DP Link,
PCL6 TP, IPDS, PDF for IPDS

HW Platform

NX Premium

Dimensions (W x D x H)

200mm x 430mm x 420mm

Weight

16KG

imagePRESS SERVER E9000

Optional/Standard

Optional

Print Resolution (dpi)

1200 x 1200, 600 x 600

Page Description Language(s)

PS3, PCL6

Memory

32GB

Hard Disk Storage

480GB (2.5"SSD),
2 x 2TB (3.5"HDD)

Processor Speed

Intel Xeon 4214 Dual, 3.20GHz, 12Core

System

FS500Pro

Fonts
138 PS fonts

Supported Operating Systems

Windows 8.1 32 and 64 bit / Windows 10
32 and 64 bit / Windows 11 / Windows
2012 R2 64 bit only / Windows Server
2016 64bit / Windos Server 2019 64bit /
Windows Server 2022 64bit / MAC OS
(10.14, 10.15, 11, 12)

Interface

2 x Ethernet (1000Base-T/100
Base-TX/10Base-T), USB3.0 x 7

Network protocols

TCP/IP (FTP, SMTP, POP, HTTP, SNMP,
LDAP, SLP, SMB, LPD, IPP, WS-Discovery,
Bonjour, Direct Mobile Printing,
Port9100, SNT, 802.1X, DHCP, DNS)

Direct Print

PDF2.0, EPS, TIFF, JDF1.8/JMF

VDP

PPML3.0, PDF/VT-1, PDF/VT-2, VPS,
FreeForm Plus

Fiery Print Controller

Fiery Command WorkStation 6 / Paper
Catalog / Fiery Spot-On / Fiery Remote
Scan / Fiery Hot Folders
Standard Features
& Virtual Printers

Fiery Print Controller Options

Fiery Impose / Fiery Compose / Fiery
Impose and Compose / Fiery Graphic
Arts Package / Removable HDD Kit

HW Platform

NX Premium

Dimensions (W x D x H)

235mm x 572mm x 527mm

Weight

22KG

Product Specifications

MAIN UNIT

| Print Specification | |
|------------------------------------|--|
| Print speed (BW/CL) | CL:135ppm, BW:130ppm |
| Recommended monthly volume | up to 1.2 million pages |
| Maximum monthly peak volume | 2.4 million page |
| Registration tolerance | Front to back: 0.5mm |
| Printing method | Colour Laser Beam Printing |
| Print resolution | 2,400 dpi x 2,400 dpi |
| Paper Supply Options | |
| Paper capacity (A4, 80gsm) | Standard: 1,000 sheets Maximum: 9,000 sheets Engine 1000 x1, POD Deck (1,000+1,000+2,000) x2 |
| Supported media types | Engine Paper Deck (1): Thin, Plain, Recycled, Color, Thick, Coated, Embossed, Bellum, Bond, OHP, Clear Film, Translucent, Label, Punched, Index*1, Synthetic POD Deck: Thin, Plain, Recycled, Color, Thick, Coated, Embossed, Bellum, Bond, OHP, Clear Film, Translucent, Label, Punched, Index*1, Synthetic *1 Index attachment is needed |
| Supported media sizes | Paper Deck 1: SRA3S, A3S, A4L, A4S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, 8KS, 16KL, 16KS, Custom (182.0x182.0mm-330.2x487.7mm) POD Deck: SRA3S, A3S, A4L, A4S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, 8KS, 16KL, 16KS, Custom (182.0x182.0mm-330.2x487.7mm) |
| Supported media weighs | Paper Deck (1): 60~500g (Coated70~500g) POD Deck: 60~500gsm (Coated70~500gsm) |
| Machine type | A3 Colour Laser Press |
| Core functions | Print |
| Processor | 1.8GHz, 1.3GHz Dual |
| Control Panel | 10.1 inch |
| Memory | 6GB |
| Hard Disk drive | SSD 1TB |
| Mirroring Hard Disk Drive | Yes |
| Interface Connection | NETWORK Standard: 1000Base-T/100Base-TX/10Base-T |
| Power <supply> | 3-phase 5-wires 380-415 V AC, 50/60 Hz, 32 A |
| Dimensions main engine | (W x D x H) 2,691 x 1,165 x 1,456 mm |
| Installation Space | (W x D) 5,218 x 1,875 (Engine, Deck, Finisher) |
| Weight | Approx. 1,065 kg |
| Consumables | |
| Toner Cartridges | Toner T14 BK / C / M / Y |

OUTPUT OPTIONS

Staple Finisher-AF1

| | |
|-------------------------|--|
| Upper Tray (A) Capacity | A4/A4R/A5R/A3/SRA3/13"x19" 1,000 sheets (60-326 gsm) / 200 sheets (326-400 gsm) / 30mm (401-500 gsm) Long sheet (Over 487.7 mm up to 762 mm length) 300 sheets (64-150 gsm) / 150 sheets (151-300 gsm) / 120 sheets (301-350 gsm) |
| Lower Tray (B) Capacity | A4 4,000 sheets (60-80 gsm) / 3,000 sheets (80.1-300 gsm), A4R 2,000 sheets (60-300 gsm), A3 1,500 sheets (60-300 gsm), SRA3 1,000 sheets (60-300 gsm), Any size 200 sheets (301-350 gsm) |
| Paper Weight | 52 to 350 gsm |
| Staple Position | Corner, Double |
| Staple Capacity A4 | 100 sheets, A3/A4R: 50 sheets |
| Dimensions (W x D x H) | 800 mm x 792 mm x 1,239 mm |
| Weight | Approx. 130 kg |
| Power | 220-240V, 50-60Hz, 8A |

Booklet Finisher-AF1

| | |
|---|---|
| Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AF1 | |
| Booklet stitch paper size | A3, A4R, SRA3, 13"x19", Free size (210 x 279.4 mm to 330.2 x 487.7 mm) |
| Booklet stitch paper weight | Body sheet 60-220 gsm, Cover sheet 64-300 gsm |
| Booklet stitch staple capacity | 25 sheets (60-80 gsm, include cover) |
| Dimensions (W x D x H) | 800 mm x 792 mm x 1,239 mm |
| Weight | Approx. 180 kg |
| Power | 220-240V, 50-60Hz, 8A |
| Non Staple Folded Bunch | up to 5 sheets Capacity(60 to 105 gsm) |
| Power Source | 100-240V, 50/60Hz, 2.8A |
| Dimensions (W x D x H) | 896 x 765 x 1,040 mm (when the extension tray is extended) |
| Weight | Approx. 110 kg |

Puncher Unit-BT1 / BU1

(Requires either the Staple Finisher-AF1 or Booklet Finisher-AF1)

| | |
|--------------------|---|
| Two or Four Holes | Punch Hole type: BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (SWE) |
| Punch Paper Weight | 60-300 gsm |
| Punch Paper Size | 2 holes: A3, A4, A4R, Free size (182 x 182 mm to 297 x 432.0 mm excluding 203 x 257 mm to 297 x 270 mm) 4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm) |

Multi Function Professional Puncher-C1

| | |
|------------------------|---|
| Paper Weight <Punch> | 75-300 gsm (Plain paper), 118-300 gsm (Coated paper) |
| <Crease> | 157-300 gsm (Plain paper / Coated paper) |
| <Through> | All substrates supported by engine |
| Paper Size <Through> | All substrates supported by engine |
| <Punch> | SRA3, A3, SRA4, SRA4R, A4, A4R |
| <Crease> | SRA3, A3, SRA4R, A4R, 13"x19", 13"x19.2", (12.6"x19.2"S, 12"x18"S, 11"x17"S, LGLS, 9"x12"S, LTRS) |
| Punch Tools | Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/ Square), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Crease |
| Dimensions (W x D x H) | 445 mm x 795 mm x 1,040 mm |
| Weight | Approx. 102kg |
| Power | 230V, 50Hz, 1.9A |

Booklet Trimmer-F1

Requires Booklet Finisher-AF1

| | |
|------------------------|--|
| Trim Width | 2-28mm |
| Trim Thickness | Up to 50 sheets (include cover) |
| Paper Weight | 52 to 300 gsm |
| Chip tray capacity | Approx. 5,000 sheets (Trim width 20mm, A4, 80 gsm) |
| Dimensions (W x D x H) | 2,095 mm (including joint, conveyor and output tray) x 790 mm x 1,040 mm |
| Weight | Approx. 178 kg (including conveyor and output tray) |

Two-Knife Booklet Trimmer-B1

Requires Booklet Trimmer-F1

| | |
|------------------------|---|
| Trim Width | 2-15 mm |
| Trim Thickness | Up to 50 sheets (include cover) |
| Paper Weight | 60 to 300 gsm (Trim 60 to 300 gsm) |
| Chip tray capacity | Approx. 1,500 sheets (Trim width 15mm, A4, 80 gsm) |
| Dimensions (W x D x H) | 2,312 mm (including Booklet Trimmer-F1) x 790 mm x 1,040 mm |
| Weight | Approx. 145 kg |
| Power | 220-240V, 60Hz, 2.3A |

Document Insertion Unit - R1

| | |
|-------------------------|---|
| Number of trays | 2 |
| Tray Capacity | Upper Tray: 200 Sheets (80 gsm), Lower Tray: 200 Sheets (80 gsm) |
| Acceptable Paper Type | Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured |
| Acceptable Paper Sizes | SRA3, A3, A4, A4R, B4, B5, B5R, Custom size (182.0 x 182.0 mm to 330.2 x 487.7 mm) |
| Acceptable Paper Weight | 52 to 300 gsm |
| Power Source | 100-240V/50/60Hz 1.0A |
| Dimensions (W x D x H) | 336 x 793 x 1,407 mm (width excluding document tray) |
| Weight | Approx. 61 kg |

Paper Folding Unit - K1

| | |
|-------------------------|--|
| Supported Folding Type | Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold |
| Acceptable Paper Type | Thin, Plain, Recycled, Colour, Bond |
| Acceptable Paper Sizes | Z-Fold : A3, A4R, B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold: A4R |
| Acceptable Paper Weight | Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold :52 to 105 gsm Double Parallel Fold : 52 to 90 gsm |
| Power Source | From the Finisher |
| Dimensions (W x D x H) | 336 x 793 x 1,190 mm |
| Weight | Approx. 71 kg |

Perfect Binder - F1

| | |
|-------------------|---|
| Booklet size | 203 x 138 mm to 297 x 216 mm |
| Booklet thickness | Up to 25mm |
| Cutting Range | Top/bottom: 6.5 to 39.5mm at each edge, fore edge: 6.5 to 49.5mm |
| Body pages | Sizes: A4, SRA4, Free size (257 x 182 mm to 320 x 228.6 mm) Paper weight and number of sheets: Thin Paper (52-63 gsm): 30-200 sheets Plain Paper (64-80 gsm): 10-200 sheets Plain Paper (81-90 gsm): 10-150 sheets Thick Paper (91-105 gsm): 10-150 sheets Thick Paper (106-163 gsm): up to 10 sheets as insertion sheet or up to 25mm as thickness of bunch |



continue from Perfect Binder - F1

| | |
|---------------|--|
| Cover | Number of Sheets: 1 sheet Sizes: A3, SRA3, Free size (257 x 364 mm to 330.2 x 487.7mm) |
| Paper weight | 90 to 300 gsm |
| Tray capacity | Approx. 127mm or approx. 1,000 sheets of paper as a total |
| Dimensions | 922 mm x 791 mm x 1,300 mm |
| Weight | Approx. 308kg |
| Power | 220-240V, 50/60Hz, 3.0A |

DFD Adapter - B1

Basic information: Enables DFD connectivity directly beside the engine

| | |
|------------------------|---|
| Paper Weight | Plain Paper 52-325 gsm, Coated Paper 128-325 gsm |
| Paper Size | 182 x 182 mm - 330.2 x 487.7 mm |
| Optionals | Finisher Bridge Height Kit 1002-A1 (Standard DFD height is 860 mm) |
| Dimensions (W x D x H) | 300 mm x 745 mm x 1040 mm |
| Weight | Approx. 60 kg |
| Power | 90-264V, 47-63Hz, more than 10A |

Finisher Bridge - A1

Basic information: Offers connectivity of Staple Finisher-AF1 PRO and Booklet Finisher-AF1 PRO with 3rd party DFD finishing equipments. Always in combination with DFD Adapter-A1.

| | |
|------------------------|---|
| Paper Weight | Plain Paper 52-325 gsm, Coated Paper 128-325 gsm |
| Paper Size | 182 x 182 mm - 330.2 x 487.7 mm |
| Dimensions (W x D x H) | 600 mm x 745 mm x 150 mm |
| Weight | Approx. 30 kg |
| Power | Power and control from DFD Adapter-A1 |

3rd Party Finishers

Basic information: The imagePRESS V1350 can be configured also with 3rd party finishers. Please find here a list of listed and approved finishers.

| | |
|-------------|--|
| Plockmatic | BLM35 Booklet Maker and Plockmatic BLM50 |
| Upgrade Kit | Plockmatic MPS (Multi-Purpose Stacker) Plockmatic BLM5000 |

Staple Cartridge

| | |
|-----------|---|
| STAPLE-N1 | for Stapling 3 x 5,000 pcs for Staple Finisher-AF1 and Booklet Finisher-AF1 |
| STAPLE-P1 | for Saddle Sticking 2 x 5,000 pcs for Booklet Finisher-AF1 |

Product images are for illustration purposes only. Certain functions are optional. Please refer to the product specifications or contact your Canon sales representative for further details.



SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place Galaxis #14-10 Singapore 138522

Tel: +65-6799 8888 | Fax: +65-6799 8882 | <https://asia.canon> | <https://sg.canon>

CANON SALES SUBSIDIARIES & BUSINESS PARTNERS

HONG KONG

Canon Hongkong Co. Ltd

5/F, Tower A, China Life Center,
18 Hung Luen Road, Hung Hom,
Kowloon, Hong Kong
Tel : 852 3191 2388
Fax : 852 2369 3800
<https://hk.canon>

PHILIPPINES

Canon Marketing (Philippines), Inc.

7/F Commerce and Industry Plaza,
1030 Campus Avenue Corner
Park Avenue, McKinley Hill,
Brgy. Pinagsama, Taguig City,
Metro Manila, Philippines 1634
Tel : 8 884-9090 / 8884-9000
<https://ph.canon>

THAILAND

Canon Marketing (Thailand) Co. Ltd

98 Sathorn Square Office Tower,
22nd - 24th Floor,
North Sathorn Road,
Silom, Bangrak,
Bangkok 10500
Tel : 66-2-344 9999
Fax : 66-2-344 9939
<https://th.canon>

MALAYSIA

Canon Marketing (Malaysia) Sdn Bhd

No.6-2-01, Canon Tower,
UOA Business Park,
Jalan Pengaturcara U1/51A,
Seksyen U1 40150 Shah Alam,
Selangor Darul Ehsan, Malaysia
Tel : 1800-88-2000
Fax : 60-3-5567 9441
<https://my.canon>

INDONESIA

PT Samafitro

Jalan Ir. H Juanda No. 8
Jakarta 10120,
Indonesia
Tel : 61-21-2949 5500
Fax : 62-21-384 4271
<https://id.canon>

VIETNAM

Canon Marketing (Vietnam) Co. Ltd

Level 10, President Place,
93 Nguyen Du, Dist 1,
Ho Chi Minh City, Vietnam
Tel : 84-8-3820 0466
Fax : 84-8-3820 0477
<https://vn.canon>

INDIA

Canon India Private Limited

7th Floor, Tower B,
Building # 5,
DLF Epitome, DLF Phase III,
Gurgaon 122002
Tel : 91-124-4160000
Fax : 91-124-4160011
<https://in.canon>

TAIWAN

Canon Marketing (Taiwan) Co. Ltd

19F, No. 100, Sec. 2
Roosevelt Road,
Taipei, Taiwan
Tel : +886-2-6632-8888
Fax : +886-2-7725-5860
<https://tw.canon>