

# XEED WUX500 Projector Specifications

Type	Imaging device, number	Reflective LCD panel (LCOS) x3
LCOS Panel	Number of pixels	1920x1200 (WUXGA)
	Size type, Aspect ratio	0.71 type, 16:10
	Driving system	Active Matrix
Projection Lens	Lens configuration	11 groups 13 elements
	F number, Focal length	F2.8, 21.7 - 39.0 mm
	Zoom magnification	1.8 times
	Projection distance	1.2 - 16.2 m
	Distance for 100 type	3.0 - 5.4 m
	Throw ratio <sup>(*)1</sup>	1.39 - 2.51
	Operation	Zoom: manual, Focus: manual, Lens shift: manual
Light Source	Power <sup>(*)2</sup>	260W / 200W
Images	Optical system	Dichroic mirror and PBS colour separation-combination system
	Brightness <sup>(*)2</sup>	5000 / 3800 lm
	Marginal lumination ratio	90%
	Contrast ratio <sup>(*)3</sup>	2000:1
	Image size (16:10)	40 - 300 type
	Lens shift	V: 0% - 60%, H: ±10% (manual)
	Electronic zoom (for length)	Max. 12x
	Keystone correction	V ±20°, H ±20°
Image Signals	Analogue PC input <sup>(*)4</sup>	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
	Digital PC input <sup>(*)4</sup>	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
	Digital video input	1080p / 1080i / 720p / 576p / 480p
	Component video input	1080p / 1080i / 720p / 576p / 76i / 480p / 480i
	HDBaseT input	Equivalent to the input signals of digital PC input and digital video input
	USB data transfer	JPEG still image
	Network communication	NMPJ screen transfer (CANON original protocol)

Terminals	DVI-I	Analogue PC / Digital PC input
	HDMI	Digital PC / Digital video input supporting Deep colour
	RJ-45 (HDBaseT)	HDBaseT input (Image, audio and control signal)
	Mini Dsub15	Analogue PC / Component video input
	Mini jack x3	Audio input x2, Audio output x1
	Mini jack x1	Wired remote control connection
	Dsub9	RS-232C connection
	USB Type A	USB connection
	RJ-45	Network connection (1000BASE-T / 100BASE-TX / 10BASE-T)
	Mechanisms	Adjustable feet
Built-in speaker		5 W, Monaural
Dimensions [mm]		W: 337, H: 118, D: 362 not including protrusion W: 337, H: 136, D: 370 (including protrusion)
Mass		5.9 kg / 13.0 lb
Noise level <sup>(*)2</sup>		37 / 30 dB
Others	Power supply	AC100 - 240 V, 50 / 60 Hz
	Power consumption <sup>(*)2</sup>	365 / 295 W
	Stand-by power consumption <sup>(*)4</sup>	1.3 / 0.6 / 0.2 W
	Operation environment	0°C - 40°C, 20%RH - 85%RH
	Storage environment	-20°C - 60°C


(\*)1: Calculated value for 100" image

(\*)2: Lamp mode is Full power / Power saver.

(\*)3: Brightness in Power saver mode is only a calculated value, and is not guaranteed as specification

(\*)4: HDBaseT only "ON" / Network only "ON" (Low-power) / HDBaseT "OFF" and Network "OFF"

KIT CONTENTS	Remote Control (RS-RC06) Computer cable Power cord
OPTIONAL PARTS	Ceiling Attachment (RS-CL14) Option Foot (RS-FT01) Remote Control (RS-RC06) Remote Control (RS-RC05)
REPLACEMENT PARTS	Lamp Assembly (RS-LP08) Replacement air filter (RS-FL02)



## Canon Offices

**MALAYSIA**  
Canon Marketing (Malaysia) Sdn. Bhd.  
Tel : 60-3-78446000  
Fax : 60-3-78450505  
www.canon.com.my

**SINGAPORE**  
Canon Singapore Pte. Ltd.  
Domestic Operations  
Tel : 65-6799-8888  
Fax : 65-6798-8882  
www.canon.com.sg

**THAILAND**  
Canon Marketing (Thailand) Co. Ltd.  
Tel : 66-344-9988  
Fax : 66-344-9861  
www.canon.co.th

**VIETNAM**  
Canon Marketing Vietnam Co. Ltd.  
Ho Chi Minh City  
Tel : 848-3820-0466  
Fax : 848-3820-0477

Hanoi  
Tel : 844-37711677  
Fax : 844-37711678  
www.canon.com.vn

## Canon Business Partners

**BANGLADESH**  
J.A.N. Associates Ltd.  
Tel : 880-2-9660601  
Fax : 880-2-8610410

**BRUNEI**  
Interhouse Company Sdn. Bhd.  
Tel : 673-2-653001  
Fax : 673-2-653003

**CAMBODIA**  
i-Click (Cambodia) Pte. Ltd.  
Tel : 855-23-996638  
Fax : 855-23-996639

**INDONESIA**  
PT Datascrip  
Canon Call Centre  
Tel : 62-21-2922-6000  
Fax : 62-21-6544811 to 13  
www.canon.co.id

**MALDIVES**  
SIMDI Company (Pvt) Ltd.  
Tel : 960-3334421  
Fax : 960-3334424

**MYANMAR**  
Myanmar Golden Rock  
International Co. Ltd.  
Tel : 001-95-1654810 to 95-1654817  
Fax : 001-95-1654820

**NEPAL**  
International Electronics  
Concern (P) Ltd.  
Tel : 977-1-4421991  
Fax : 977-1-4421909

**PAKISTAN**  
Shirazi Trading Co. (Pvt) Ltd.  
Tel : 92-21-32417737, 32417746  
Fax : 92-21-32417747

**SRI LANKA**  
Metropolitan Office (Pvt) Ltd.  
Tel : 94-114-700-200  
Fax : 94-114-700-398

Dealer's Stamp

0196W739

# Canon

**SOUTH & SOUTHEAST ASIA  
REGIONAL HEADQUARTERS**

**CANON SINGAPORE PTE. LTD.**

1 HarbourFront Avenue,  
#04-01 Keppel Bay Tower, Singapore 098632

www.canon-asia.com

# XEED

COMPACT INSTALL MULTIMEDIA PROJECTOR

# Canon

Delighting You Always



# GLORIOUS PERFORMANCE GREATER EASE OF USE



**XEED WUX500**  
MULTIMEDIA PROJECTOR



Powerful, Consistent  
5000lm Brightness



Easy HDBaseT Setup  
and Cost Savings



Wireless LAN  
Convenience



Precise Imaging  
Capabilities and  
Correction



Simple PC-less Usage

# Impressive Possibilities are Easy



## XEED WUX500 LCOS Compact Install

The XEED WUX500 is a powerhouse projector in a compact install package. Every image and video comes out breathtaking – in 1920 x 1200 WUXGA resolution and 5000 lumens of brilliance – optimised by LCOS and Canon's proprietary AISYS technology. Together with the new HDBaseT receiver for easy set-ups and significant cost savings, and Wi-Fi, network and PC-less connectivity, powerful new experiences present themselves each time you use the XEED WUX500.


### Powerful, Consistent 5000lm Brightness

#### AISYS Optical Engine with LCOS Technology


In the XEED WUX500, Canon's AISYS optical system delivers a powerful 5000 lumens of brightness and a vivid contrast ratio of 2000:1 for the clearest images, even in high ambient light levels. LCOS panels work together with the AISYS system to create smooth, seamless images and accurate colours, without any distracting 'lattice' or 'grid' effects.



LCOS Projection



Conventional Projection




#### Constant f/2.8 Aperture for Full 5000lm Brightness

The projection lens in the XEED WUX500 is engineered to maintain a constant aperture of f/2.8 across its 1.8x zoom range. This enables the projector to consistently maintain its full 5000lm brightness, regardless of zoom position.

### Easy HDBaseT Setup and Cost Savings

The XEED WUX500 is equipped with an HDBaseT receiver port that supports uncompressed HD media, audio, and control signals – all through a single LAN cable, and across 100m. This greatly improves convenience in system configuration, and saves cost by eliminating the need for costly HD cables, signal boosters and repeaters. Simply connect multiple sources to an HDBaseT transmitter, then link to the XEED WUX500 using an inexpensive LAN cable, and the set-up is complete.



### Wireless LAN Convenience and NMPJ Modes


#### Wireless LAN Connections

Enjoy enhanced convenience and control with the various connection set-ups for projecting your images and videos (without audio). If the projector is connected to a network, it can be configured as a wireless or wired LAN infrastructure mode. Alternatively, the projector can act as a receiver for direct wireless connection from a PC. You can also use NMPJ to link up multiple machines in different ways.



#### Network Multi Projection (NMPJ)


Using NMPJ, you have different display modes to match various communications requirements. To facilitate meetings, lectures and broadcasting, users can easily share and project data from multiple sources via a network.



### Precise Imaging Capabilities and Correction

In multi-projector displays or when projecting from an angle, the XEED WUX500 deploys adjustment and calibration technologies to produce high image fidelity and accuracy.

#### Edge Blending



Built-in edge blending and registration adjustments seamlessly blend images from multiple projectors.

#### 4-point Keystone Correction




Automatically ensures an undistorted image that is sharp and precise, even when projecting diagonally.

### Simple PC-less Usage

Have effortless flexibility and control with the PC-less abilities of the XEED WUX500, which lets you project JPEG content directly from a USB flash drive for a wide range of display options. Supporting ease of use are functions that include a built-in thumbnail display and a wide range of animation effects.

#### PC-free Multi-projection

Just input data directly via USB to project a single image using multiple projectors.



#### Greater Projection Versatility

Take advantage of the XEED WUX500 for business presentations, events, gallery displays, digital signage, and more.

