



Vivid Colour, Professional Impact.

Add a touch of details to your business documents with the imageCLASS LBP670 II Series—where vibrant colour meets seamless productivity. Create impressive visuals for presentations, reports, or marketing drafts ensuring every document resonates and leaves a lasting impression.

UP TO
33 PPM (A4)
FAST PRINT
SPEED

QUICK
7.1 SEC
FIRST PRINT
OUT TIME

V² COLOUR

UP 7,600
PAGES
HIGH-YIELD
CARTRIDGE

COLOUR
UP 5,500
PAGES
HIGH-YIELD
CARTRIDGE



MAINTAIN PRODUCTIVITY

With quick first print-out times and automatic duplex printing, keep your workflow smooth and efficient.



WIFI CONNECTIVITY

Built-in Wi-Fi enables smooth and efficient connectivity across devices, allowing flexible print sharing within any work environment.



EASY MAINTENANCE

All-in-one toner cartridges simplify printer maintenance. High-yield cartridge options reduce the need for frequent replacements - saving time, effort and lowering cost per page.



ENHANCED DATA PROTECTION

TLS 1.3 and WPA3 helps to safeguard against unauthorised access and defend system integrity from sniffing, spoofing, and tampering.

SPECIFICATIONS

PRINT			imageCLASS LBP674Cx II	imageCLASS LBP673Cdw II
			-	•
Printing Method A4*1(mono/colour)		(colour)	Colour Laser Beam Printing	
Print Speed	A4*1 (mono/colour)		33 / 33 ppm	
rillic Speed	Letter*1 (mono/colour) 2-Sided, A4 (mono/colour)		35 / 35 ppm 29 / 29 ipm	
Print Resolution		(IIIOIIO/COIOOI)	600 x 600 dpi	
Print Quality with Image Refinement Technology		hnology	1,200 x 1,200 dpi (equivalent)	
Warm-Up Time (From Power On)			14 sec or less	
First Print Out Time (FPOT)		A4 (mana/salaur)	7.1 / 7.1 sec	
(Approx.)*2				
Print Language			UFR II, PCL 6, Adobe® PostScript® 3™	
Auto Duplex Print			Yes	
Print Margins			Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)	
Supported File Format for	USB Direct Pri	nt	JPEG, TIF	FF, PDF
PAPER HANDLING				
	Cassette		250 Sheets	
Input Tray Capacity (Plain Paper, 80 g/m²)	Standard	Multi Purpose Tray	50 Sheets	
	Optional	Paper Feeder	550 Sheets	
	Maximum		850 sheets (Cassette + 1 Paper Feeder)	
Output Tray Capacity (Plain Paper, 80 g/m²)		/m²)	150 Sheets	
	Cassette		A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Envelope (COM10, Monarch, DL, C5),	
			Envelope (COMIO, Monarch, DL, C5), Custom (Min. 98.0 x 148.0 mm to Max. 216.0 x 356.0 mm)	
			A4, A5, A6, Legal, Letter, Foolscap, Indian Legal,	
Media Size	Paper Feeder		Custom (Min. 100.0 x 148.0 mm to Max. 216.0 x 356.0 mm)	
	Multi Purpose Tray		A4, A5, A6, Legal, Letter, Foolscap, Indian Legal, Index Card, Envelope (COM10, Monarch, DL, C5),	
			Custom (Min. 76.0 x 127.0 mm to Max. 216.0 x 356.0 mm)	
	2-Sided Printing		A4, A5, Legal, Letter, Foolscap, Indian Legal,	
			Custom (Min. 148.0 x 148.0 mm to Max. 216.0 x 356.0 mm)	
Media Type Cassette / Paper Feeder		Damas Faadas	Plain Paper, Recycled Paper, Colour Paper, Bond Paper 60 - 200 g/m²	
Media Weight Multi Purpose Tray			60 - 200 g/m²	
CONNECTIVITY & COS		ise iray	80 - 200	5 9/111-
CONNECTIVITY & SOFTWARE			USP 20. 10Page T/100Page TV/100Page T	
Standard Interface	Wired		USB 2.0, 10Base-T/100Base-TX/1000Base-T Wi-Fi 802.11b/q/n	
	Wireless		(Infrastructure Mode, Access Point, WPS)	
Network Protocol	Print		LPD, RAW, IPP, IPPS, WSD-Print (IPv4, IPv6)	LPD, RAW, WSD-Print (IPv4, IPv6)
	TCP/IP Application Services		mDNS, DHCP, Auto IP	(IPv4), DHCPv6 (IPv6)
	Management		SNMP v3 (IPv4, IPv6), HTTP/HTTPS, SNTP	
	Wired		IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3	
Network Security	Wireless		Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES)	
received in Second			WPA3-SAE(AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES)	
			WPA3-SAE(AES)	
Mobile Solution			Canon PRINT app, AirPrint®, Mopria® Print Service, Microsoft Universal Print	
Compatible Operating System*3			Windows®, Windows Server®, ۱	macOS®, Linux, Chrome OS™
Other Features			Department ID, Secure Print, Application Library	Department ID, Secure Print
Available Software			Printer Driver,	Toner Status
GENERAL				
Device Memory			16	В
Storage (eMMC)	-		2 G	В
Display			5" LCD Touchscreen	5-Line LCD
Power Requirements			AC 220 - 240 V, 50/60 Hz	
Power Consumption (Approx.)	Operation		700 W (max. 1,380 W)	
	Standby		24 W	
	Sleep		1W	
Operating Environment Temperature Humidity		e	10 - 3	
			20 - 80% RH (no condensation)	
Monthly Duty Cycle*4			50,000 pages	
Dimensions (WxDxH)			425 x 427 x 380 mm	425 x 427 x 300 mm
Weight*5 (Approx.)			16.1 kg 15.5 kg	
	Standard		Cartridge 069 BK: 2,100 pages (bundled: 1,200 pages) Cartridge 069 CMY: 1,900 pages (bundled: 1,100 pages)	
Toner Cartridge*6	High			
			Cartridge 069H BK: 7,600 pages Cartridge 069H CMY: 5,500 pages	
OPTIONAL ACCESSORI	ES			
Paper Feeder			Paper Feeder PF-K1 (550 sheets)	
Barcode Printing			Barcode Printing Kit-E1E	-

Specifications are subject to change without notice.

- "Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.

 "I First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.

 "I The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the https://asia.canon/en/support website when available.

- *4 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month
- *5 Excluding toner cartridge.
 *6 Toner cartridge yield is in accordance with ISO/IEC 19798.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS **CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.