




# Compact Wireless All-In-One for Low-Cost Printing









# **LOW-COST CARTRIDGES**

Experience unmatched value with our low-cost cartridges, providing exceptional quality prints without sacrificing affordability.



# **AUTO POWER ON/OFF**

Intelligently power ON upon receiving a print command and switches off when not in use, conserving energy and optimising your workflow.



#### **MOBILE & CLOUD PRINTING**

Print from smartphones, tablets, laptops and cloud storage with the free Canon PRINT and Canon Easy-PhotoPrint Editor apps.



SPECIFICATIONS / PIXMA E470					
PRINT	Maximum Printing Resolution			4,800 (horizontal)*1 x 1,200 (vertical) dpi	
	Print Speed <sup>-2</sup> (approx.) ESAT/Simplex (Mono/Colour)		(Mono/Colour)	8 / 4 ipm	
SCAN*3	Scanner Type			Flatbed (Platen)	
	Scanner Technology			Contact Image Sensor (CIS)	
	Optical Resolution*4			600 x 1,200 dpi	
	Maximum Document Size	ument Size Flatbed		A4, LTR (216 x 297 mm)	
СОРУ	Copy Speed"5 (approx.)	Colour	sFCOT/Simplex	28 sec	
			sESAT/Simplex	2.1 ipm	
	Maximum Copies			21 pages	
	Maximum Document Size			A4, LTR	
ق	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m²)	Up to 60 sheets	
DLIN			Photo Paper (4 x 6")	Up to 20 sheets	
PAPER HANDLING	Media Size	Rear Tray		A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", Envelope (COM10, DL), Square (127 x 127 mm)  Custom Size:  Width: 101.6 - 215.9 mm, Length: 152.4 - 676 mm)	
	Media Type	Rear Tray		Plain Paper (64 - 105 g/m²) Photo Paper Plus Glossy II (PP-201, PP-208)	
AENTS US	Operating System Compatibility	Please visit https://asia.canon/support to confirm OS compatibility and to download the latest drivers.		Windows 10 / 8 / 7 SP1 / Vista SP2*6 macOS 10.8.5 or later	
	Connectivity	Network		Wireless LAN IEEE802.11b/g/n	
		Interface		USB 2.0	
UIRE	Carron Drinking Asses	Mobile		Canon PRINT, Easy-PhotoPrint Editor, Creative Park	
REG	Canon Printing Apps	Others		PosterArtist Lite, PosterArtist (Web)	
STEM L SPE	Mobile/Cloud Printing Solutions			Canon Print Service (Android), Cloud Service	
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Power			AC 100 - 240 V, 50/60 Hz	
	Power Consumption*7 (approx.)			10 W (Standby: 1.6 W)	
	Recommended Monthly Print Volume			50 - 200 pages	
	Dimensions (WxDxH) (approx.)			426 x 306 x 145 mm	
	Weight (approx.)			3.5 kg	
CONSUMABLES		Type/Colours		Pigment Ink / Black Dye-Based Ink / Colour	
	Ink Cartridges Page Yield*		Plain Paper	A4 Colour Documents <sup>-</sup> °: PG-47: 400 / CL-57S: 180 Optional: CL-57: 300	

# ${\bf Specifications} \ {\bf are} \ {\bf subject} \ {\bf to} \ {\bf change} \ {\bf without} \ {\bf notice}.$

- \*1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- \*2 Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.

  Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

  Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- \*3 TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- \*4 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- \*5 Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.
  Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- $^{*}6\,$  Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- \*7 Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings. Copy: When copying ISO/JIS-SCID N2 on A4 size plain paper using default settings.
- \*8 Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
- \*9 Declared yield value is in accordance with ISO/IEC 24711, using the ISO/IEC 24712 colour chart. Values obtained by continuous printing.



# SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel : 65-6799-8888 | Fax : 65-6799-8882 | https://asia.canon

DEALER'S STAMP	This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.