Made to _Impress_

Available in Black and Purple

Multifunction Refillable Ink Tank Printer with Low-Cost Ink Bottles

UP TO
8,100*
COLOUR PAGES

UP TO
7,600*
MONO PAGES

*Economy Mode

COMPATIBLE
WITH
**LOW-COST
INK BOTTLES**

This high-performance 3-in-1 printer combines low-cost printing and maintenance together, alongside being compatible with low-cost ink bottles for greater cost efficiency.

COMPATIBLE LOW-COST INK BOTTLES

Small and standard ink bottles are available to meet the different requirements in print volume.

*Published highest yield is achievable based on Standard ink bottle and printing on Economy mode. For more details, refer to specifications on underside of leaflet.

EASY, HASSLE-FREE INK REFILLING

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.

EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.

COMPACT, SPACE SAVING FOOTPRINT

The printer's compact footprint allows it to fit into tight spaces with ease.

IMAGING **POSSIBILITIES & BEYOND**

SPECIFICATIONS / PIXMA G2730

PRINT	**Maximum Printing Resolution**[*1]			4800 (horizontal) x 1,200 (vertical) dpi
	Print Speed[*2]	**ESAT/Simplex (Mono/Colour)**		11 / 6 ipm
		FPOT Ready/Simplex (Mono/Colour)		9 / 14 sec
		Photo (4 x 6")		45 sec
SCAN[*3]	**Scanner Type**			Flatbed
	Scanning Method			Contact Image Sensor (CIS)
	Optical Resolution[*4]			600 x 1,200 dpi
	Maximum Document Size			A4, LTR (216 x 297 mm)
COPY	**Copy Speed**[*5]	**Colour**	**sFCOT/Simplex**	23 sec
			sESAT/Simplex	2.7 ipm
	Maximum Copies			21 pages
	Maximum Document Size			A4, LTR
PAPER HANDLING	**Maximum Input Capacity**	**Plain Paper (64 g/m²)**		Up to 100 sheets
		Photo Paper (4 x 6")		Up to 20 sheets
	Media Size			A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)
	Media Type			Plain Paper (64 – 105 g/m²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208/PS-808) Envelope
SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	**Operating System Compatibility**	Please visit https://asia.canon/support to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1[*6] macOS 10.14.6 – 12 or later Chrome OS
	Interface			USB 2.0
	Power			AC 100 – 240 V, 50/60 Hz
	Power Consumption[*7]			15 W (Standby: 0.6 W)
	Duty Cycle			Up to 3,000 pages/month
	Recommended Monthly Print Volume			150 – 1,500 pages
	Dimensions (W x D x H)	**Factory Configuration**		416 x 337 x 177 mm
		Output/ADF Trays Extended		416 x 557 x 268 mm
	Weight			6 kg
CONSUMABLES	**Ink Bottles**	**Size**	**Standard / Small**	GI-71 / GI-71S (Bundled)
		Type/Colours		Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow
		Page Yield[*8]	**Plain Paper**	A4 Colour Documents[*9] GI-71 PGBK: 6,000 (Economy Mode[*10]: 7,600) GI-71 C, M, Y: 7,700 (Economy Mode[*10]: 8,100) GI-71S PGBK: 3,100 (Economy Mode[*10]: 3,900) GI-71S C, M, Y: 4,400 (Economy Mode[*10]: 4,600)
			Photo Paper (PP-201)	4 x 6" Photos[*11]: GI-71 PGBK: NA / GI-71 C, M, Y: 2,200 GI-71S PGBK: NA / GI-71S C, M, Y: 1,200
	User Replaceable Maintenance Cartridge			MC-G04

Specifications are subject to change without notice.

[*1] Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

[*2] Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.
Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

[*3] TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

[*4] Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.

[*5] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735.
Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.

[*6] Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

[*7] When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

[*8] Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
Package contains GI-71S (Black, Cyan, Magenta, and Yellow) ink bottles.

[*9] Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup.
The colour yield is based on 1 set of composite colour bottles.

[*10] The Economy mode reduces the ink consumption by lowering the density. More pages can be printed using this mode.

[*11] Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial setup.
Black ink is not used when printing under this condition. However, a minimal amount of black in is used for maintenance purposes.

DEALER'S STAMP