

Stay Ahead with Quality Prints and Robust Security Features



Drive productivity and streamline daily operations with a high-speed A3 colour multifunction device engineered for busy corporate offices.

With intelligent features that simplify complex workflows, robust 360-degree security to protect sensitive data, and outstanding print quality, it empowers teams to work faster, smarter, and with complete confidence.

From high-volume data reports to vivid sales presentations, expect a print performance that meets the standard your business requires.



CONNECTIVITY

Enhance teamwork and boost productivity no matter where your teams are located. Integrate seamlessly to cloud platform and business tools, to keep your team aligned and connected.



RELIABILITY

Enable uninterrupted workflows, deliver consistent performance, and gain full visibility and control over print operations. Drive greater efficiency, time savings, and cost optimisation.



SECURITY

Documents, networks and device are protected by a range of comprehensive security features, including Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery, Dual network and WPA3 support.



SUSTAINABILITY

Energy-efficient device built with up to 30% recycled plastics and up to 5% steel. Replacing plastic packaging with recyclable cardboard helps to reduce plastic waste.

imageFORCE C3026

Main Unit

Machine Type

A3 Color Multifunctional

Processor

Dual Core Processor

Core Functions

Print, Copy, Scan, Send and Optional Fax

Control Panel

7-inch TFT LCD WVGA Colour Touch panel

Memory

Standard: RAM 3.0 GB

Storage

Standard: 64 GB eMMC (available space 30 GB)

Optional: 256 GB SSD

Interface Connection

Network:

Standard: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Others:

Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Optional: Copy Control Interface

Paper Supply Capacity (A4, 80 gsm)

Standard: 1,200 sheets

100 sheets: Multi-purpose tray x1

550 sheets: Standard Cassette x2

Maximum: 2,300 sheets (with Cassette Feeding
Unit-BB1)

Paper Output Capacity (A4, 80 gsm)

Standard: 250 sheets

Maximum: 645 sheets (with Inner Finisher-N1 and
Copy Tray-T2)

Supported Media Types

Multi-purpose Tray:

Thin, Plain, Recycled, Colour, Heavy, Coated*, Tracing,
Bond, Transparency, Labels, Pre-punched,
Letterhead, Envelope

*257-300 gsm requires Media Adjustment Kit-A1

Upper Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency,
Pre-punched, Letterhead, Envelope*

*Envelope Feeder Attachment B (standard) is required
except ISO-C5

Lower Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency,
Pre-punched, Letterhead, Envelope*

*Envelope Feeder Attachment A (standard) is required

Supported Media Sizes

Multi-purpose Tray:

Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4,
B5, B5R

Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm

Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm

Envelopes: COM10 No.10, Monarch, ISO-C5, DL

Envelope custom size: 98.0 x 98.0 mm to
320.0 x 457.2 mm

Upper Cassette:

Standard size: A4, A5, A5R, A6R, B5

Custom size: 105.0 x 148.0 mm to 297.0 x 215.9 mm

Envelopes: ISO-C5

Lower Cassette:

Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R

Custom size: 105.0 x 148.0 mm to 304.8 x 457.2 mm

Envelopes*: COM10 No.10, Monarch, DL

*Envelope Feeder Attachment A (standard) is required

Supported Media Weights

Multi-purpose Tray:

52 to 300 gsm (Only 60 to 300 gsm supported with
Media Adjustment Kit-A1*)

*Media Adjustment Kit-A1 is required for Coated
(257-300 gsm)

Upper/Lower Cassette:

52 to 256 gsm

Duplex:

52 to 220 gsm

Warm-up Time (Quick start mode: ON)

4 seconds or less*

*Time from device power-on to when the copy icon
appears and is enabled to operate on the touch panel
display.

From Power On: 10 seconds or less*

*Time from device power-on, until copy ready (not print
reservation)

From Sleep Mode: 10 seconds or less

Dimensions (W x D x H)

With Platen Cover-Y3: 565 x 712 x 788 mm

With Single Pass DADF-F1: 565 x 712 x 862 mm

Installation Space (W x D)

Basic: 978 x 1,141 mm (right door & multi-purpose tray
opened + paper cassette opened)

Fully Configured: 1,285 x 1,141 mm (with Single Pass
DADF-F1 + Inner Finisher tray max
extended + Copy Tray T-2 max
extended + paper cassette opened)

Weight Including Regular Toner

With Platen Cover-Y3: Approx. 73 kg

With Single Pass DADF-F1: Approx. 79 kg

Print Specifications

Print Speed (BW)

1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

2-sided: Up to 26 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

Print Resolution (dpi)

4800 x 2400 dpi

Page Description Languages

Standard: UFR II, PCL6/PCL5

Optional: Adobe PostScript 3

Direct Print

PDF, EPS, TIFF/JPEG, XPS

Printing from Mobile and Cloud

AirPrint, Mopria, IPP Everywhere, Canon PRINT,
uniFLOW Online and Universal Print

OS Standard Printing

Android, Windows® 11, Chrome OS, macOS (11.2.2 or
later), iOS (15.2 or later), iPadOS

Fonts

PS fonts: 136 Roman

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T¹ (Japanese,
Korean, Simplified and Traditional Chinese),
Barcode fonts²

¹Optional PCL International Font Set-A1 is required

²Optional Barcode Printing Kit-D1 is required

Operating System

UFR II: Windows® 11/Server2016/Server2019/
Server2022/Server2025, macOS (11.7 or later)

PCL: Windows® 11/Server2016/Server2019/
Server2022/Server2025

PS: Windows®11/Server2016/Server2019/Server2022/
Server2025, macOS (11.7 or later)

PPD: Windows® 11, macOS (11.7 or later)

As of Mar 2026

Copy Specifications

Print Speed (BW and CL)

1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

2-sided: Up to 26 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

First-Copy-Out Time (A4, BW/CL)

Approx. 7.0/8.7 seconds or less

Copy Resolution (dpi)

600 x 600 dpi

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25 % to 400 % (1 % Increments)

imageFORCE C3026

Scan Specifications

Type

Standard: Color Platen

Optional: Platen Cover-Y3, Single Pass DADF-F1*
[2-sided to 2-sided]

DADF: Duplexing Automatic Document Feeder

*Multi-Sheet Feed Detection is supported

Document Feeder Paper Capacity (80 gsm)

Up to 100 sheets

Document Feeder Acceptable Paper Weight

Document Feeder media weight:

1-sided scanning: 38 to 128 gsm

2-sided scanning: 50 to 128 gsm

Supported Media Sizes

Platen: Max. scanning size: 297.0 x 431.8 mm

Document Feeder media size:

A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6, B6R

Custom size: 48.0 x 85.0 mm to 304.8 x 431.8 mm

Scan Resolution (dpi)

600 x 600 dpi

Scan Speed (ipm, BW/CL, A4)

Single Pass DADF-F1:

1-sided scanning: 80/80 (300 x 300 dpi, send),
60/60 (600 x 600 dpi, copy)

2-sided scanning: 120/120 (300 x 300 dpi, send),
60/60 (600 x 600 dpi, copy)

Pull Scan Specifications

Color Network ScanGear 2. For both TWAIN and WIA

Supported OS: Windows®11/Server 2016/

Server2019/Server 2022/Server 2025

As of Mar 2026

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP*), SMB, FTP,
SFTP, WebDAV

Optional: Super G3 FAX

*Available OAuth 2.0 authentication method on
Microsoft Exchange Online and Google Workspace

Address Book

LDAP (2,000)/ Local (1,600) /Speed dial (200)

Communication Protocol

File: FTP (TCP/IP), SFTP (TCP/IP), SMB3.1.1 (TCP/IP),
WebDAV

E-mail/iFax: SMTP (send), POP3 (receive)

File Format

Standard: TIFF (MMR), JPEG*, PDF (Compact,
Searchable, PDF/A-1b, PDF/A-1a, PDF/A-2a,
PDF/A-2b, PDF/A-2u, PDF/A-3a, PDF/A-3b,
PDF/A-3u, Encrypted, Device Signature), XPS
(Compact, Searchable, Device Signature),
Office Open XML (PowerPoint, Word)

Optional: PDF (Trace & Smooth), PDF/XPS
(User Signature)

*Single-page only

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 dpi (Ultra Fine), 200 x 400 dpi (Superfine),

200 x 200 dpi (Fine), 200 x 100 dpi (Normal)

Sending/Receiving Size

Sending: A3, A4, A4R, A5¹, A5R¹, B4, B5², B5R¹

Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R

¹Sent as A4

²Sent as B4 short

FAX Memory

Up to 30,000 pages (2,000 jobs)

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 256 addresses

Memory Backup

Yes

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

Power Source

220-240V, 50/60Hz, 4A

Power Consumption

Maximum: Approx. 1,500W

Sleep Mode: Approx. 0.8W*

*0.8W is not available in all circumstances due to
certain settings.

Consumables

Toner Cartridges

NPG-1007 Toner BK/C/M/Y

NPG-1007L Toner C/M/Y

Toner (Estimated Yield @ 5 % Coverage)

NPG-1007 Toner BK: 36,000 pages

NPG-1007 Toner C/M/Y: 19,000 pages

NPG-1007L Toner C/M/Y: 2,500 pages

Configuration Output Options*



Platen Cover-Y3

- Single document scanning



SP DADF-F1

- Multiple document scanning
- 100 sheet duplexing automatic document feeder
- Scans up to 80 ipm (1-sided, 300 dpi) and 120 ipm (2-sided, 300 dpi)



Inner Finisher-N1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)



Inner 2 Way Tray-M1

- Separates copies, prints and faxes
- Adds a second internal output tray



Utility Tray-B1




Copy Tray-T2



imageFORCE PEDESTAL 31

- Raises the device, no additional media supply



Cassette Feeding Unit-BB1

- Supports up to A3
- Media weight 52-256 gsm
- 2 x 550 sheets (80 gsm)

*Paper capacity may vary with different paper type/size.



Partner / Dealer Stamp

To arrange for a demonstration, simply contact our office below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "eMaintenance" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2026 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.