



Built for **Business**

Compact A4 Desktop Scanner for All Your Business Scanning Needs

Automate your business' information capture processes efficiently with the small but mighty imageFORMULA DR-M140II. With up to 1,200 dpi output resolution, this compact workhorse captures everything from business cards to glossy magazines with speed and accuracy.

UP TO
40 PPM | 80 IPM*
FAST SCAN SPEED
*300 dpi, A4


SCAN UP
TO A2*
*With Folio scan,
Long Document mode

UP TO
1,200 DPI
SCAN OUTPUT
RESOLUTION

80
80-SHEET
FEEDER

Compact Space-Saving Design

The U-turn path mode enables full-front operation, while saving space when placed on countertops or tight spaces.



Fast and High-Quality Scanning

The DR-M140II scanner offers impressive image quality and fast capture speeds that maximise productivity, allowing you to scan with the utmost confidence.



Versatile Media Handling

Capable of handling media of wide-ranging textures and thicknesses, the DR-M140II is simple and quick to set up. Swift scanning of paper documents, receipts, IDs, and business cards is possible with just a touch of a button.



SPECIFICATIONS / DR-M140II

SCANNING		
Type		Desktop Sheet-Fed Scanner
Scanning Speed ^{*1}	Greyscale	200 dpi: 40 ppm (Simplex) / 80 ipm (Duplex) 300 dpi: 40 ppm (Simplex) / 80 ipm (Duplex)
	Colour	200 dpi: 40 ppm (Simplex) / 80 ipm (Duplex) 300 dpi: 40 ppm (Simplex) / 80 ipm (Duplex)
Scanning Element		Contact Image Sensor (CIS)
Light Source		LED
Scanning Side		Simplex / Duplex
Scanning Modes		Black and White, Error Diffusion, 256-level Greyscale, Active Threshold, Advanced Text Enhancement, Advanced Text Enhancement II, 24-bit Colour
Scanning Features		Folio Scanning, Double Feed Release, 2D / Barcode
Optical Resolution (Max.)		600 dpi
Output Resolution ^{*2}		100, 150, 200, 240, 300, 400, 600, 1200 dpi
MEDIA HANDLING		
Document Size	Plain Paper	Width: 50.8 to 216 mm Length: 54 to 356 mm (Up to 5,588 mm long with Long Document mode)
	Business Card	Width: 50.8 to 55 mm Length: 85 to 91 mm
	Card (ISO Standard)	54 x 86 mm
Document Thickness and Weight	Plain Paper	U-turn Path: 27 to 128 g/m ² (0.04 to 0.15 mm) Straight Path: 27 to 255 g/m ² (0.04 to 0.3 mm)
	Business Card	380 g/m ² (0.45 mm) or smaller (Use the straight path and place vertically)
	Card	0.76 mm or less, 1.4 mm or less for the embossment (Use the straight path and place vertically)
Auto Document Feeder Capacity ^{*3}		80 sheets
CONNECTIVITY & SOFTWARE		
Interface		Hi-Speed USB 2.0
Software		ISIS / TWAIN / WIA Drivers, CaptureOnTouch
GENERAL		
Power Requirements		AC 100 - 240 V (50 / 60 Hz)
Power Consumption	Scanning (Max.)	24.5 W
	Sleep Mode	1.6 W
	With Power Switched OFF (Max.)	0.1 W
Operating Environment	Temperature	10 to 32.5°C
	Humidity	20 to 80% RH
Dimensions (W x D x H)	When Trays Are Closed	313 × 181 × 93 mm
	When Trays Are Opened	313 × 250 × 165 mm
Weight (Approx.)		2.6 kg (Without AC adapter)
CONSUMABLES & ACCESSORIES		
Options / Consumables		Exchange Roller Kit
Accessories		Flatbed Scanner Unit 102, Flatbed Scanner Unit 201

Specifications are subject to change without notice.

^{*1} Based on A4 portrait document size.

^{*2} Primary scan lines x secondary scan lines.

^{*3} Size: A4 or smaller (Same type document only), Paper Weight: 70 to 100 g/m², Temperature: 15 to 27.5°C, Humidity: 25 to 75% RH, Total Thickness: 10 mm or less.



**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.**

438A Alexandra Road, #06-10, Alexandra Technopark, Singapore 119967
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.